


STANDARD LEADER LINE RULES AND SAMPLES

DRAW LEADERS WITH SAME ANGLES AND ALIGN ANGLES VERTICALLY WHEN POSSIBLE SEE NOTE 3

LEADER ARROWS SHALL BE CONSISTENT THROUGHOUT EACH DRAWING OF THE PLAN SET, SEE NOTE 4


DRAW LEADERS WITH SAME ANGLES AND ALIGN ANGLES VERTICALLY WHEN POSSIBLE SEE NOTE 3



LEADERS SHALL NOT CROSS DIMENSIONS




LEADERS SHALL NOT CROSS OTHER LEADERS




LEADERS SHALL NOT BE DRAWN AT THE SAME ANGLE AS THE PATTERN




TYPICAL LEADER LINE ANGLE SETTINGS



45° ANGLE



30° ANGLE



15° ANGLE

NOTES:

1. REFER TO SECTION 1.1 OF THE DESIGN GUIDE
2. LEADER LINES SHALL BE USED FOR ASSOCIATING TEXT TO AN OBJECT
3. LEADER LINES SHALL BE AS CONSISTENT AS POSSIBLE THROUGHOUT THE ENTIRE DRAWING
4. LEADER ARROWS SHALL BE THE SAME AS FONT SIZE WITH CONSISTENCY THROUGHOUT THE PLAN SET

APPROVED:

DISTRICT ENGINEER \_\_\_\_\_ DATE \_\_\_\_\_

LATEST REVISION \_\_\_\_\_ DATE \_\_\_\_\_

DESIGN GUIDE EXHIBIT 'B'

STANDARD LEADER LINES FOR CONSTRUCTION DRAWINGS

VALLEY CENTER MUNICIPAL WATER DISTRICT  
29300 VALLEY CENTER ROAD  
VALLEY CENTER, CA 92082



F:\Engineering\Civil\3018\Design Guidelines\Design Guide Exhibits.dwg Mar 10, 2020 - 7:29am