


CROSSING (PERPENDICULAR) CONDITION



NOTES:

PARALLEL CONDITION

- ZONE "A" NO SEWER SHALL BE CONSTRUCTED WITHOUT SPECIAL APPROVAL FROM STATE DEPARTMENT OF HEALTH SERVICES.
- ZONE "B" SEWER SHALL BE CONSTRUCTED OF EXTRA STRENGTH VITRIFIED CLAY PIPE WITH COMPRESSION JOINTS, POLYVINYL CHLORIDE PLASTIC PIPE WITH RUBBER RING JOINTS (PER ASTM D 3034), OR DUCTILE IRON PIPE WITH COMPRESSION JOINTS.
- ZONE "C" SEWER SHALL BE CONSTRUCTED OF DUCTILE IRON PIPE WITH APPROVED COATING

 & "D" AND MECHANICAL JOINTS OR CONTINUOUS SECTION OF CLASS 200 (DR14 PER AWWA C-900)
 POLYVINYL CHLORIDE PLASTIC PIPE CENTERED OVER PIPE BEING CROSSED.
- ZONE "P" NO SEWER LINE CONSTRUCTION ALLOWED.
- UPON APPROVAL FROM DISTRICT ENGINEER HDPE FUSION WELDED PIPE MAY BE USED AS A CASING WHEN MINIMUM JOINT DISTANCE CAN NOT BE MET.
- ANY SEPARATION LESS THAN 10 FT REQUIRES COUNTY DEPARTMENT OF ENVIRONMENTAL HEALTH AND DISTRICT APPROVAL.

APPROVED: 3/2/2010

TO THE

VALLEY CENTER MUNICIPAL WATER DISTRICT STANDARD DRAWING

PIPELINE SEPARATION REQUIREMENTS

NOT TO SCALE

DWG. NUMBER

S-3

District Engineer

Date

3/2/2020 Latest Revision Date